AERUS ENTERPRISE S O L U T I O N S

Product Catalog & Specifications Book



Table of Contents

Air Scrubber by Aerus
Induct 500
Induct 750
Induct 2000
Induct 5000
Induct 10000
AP3000
AP50010
Air Scrubber Mini EM by Aerus
PureCloud
G4 Whole Home Filtration
Laundry Pro 2.0
Air Scrubber Mobile by Aerus



description

- · Duct or plenum installed natural air system
- Discreet or concealed installation
- UV bulb monitoring indicator included
- Low maintenance no cleaning required

applications

- Purifies the air and reduces particles that can irritate allergies and asthma
- Protects people from dangerous contaminants, pollutants and protects heating/cooling systems from dust buildup
- HVAC systems with accessible ducts
- Residential and commercial use
- Apartments
- Offices

the technology

The Air Scrubber by Aerus substantially reduces odors, visible smoke in the air, and microbial populations on **surfaces***, utilizing the patent pending ActivePure® Technology. ActivePure consists of a special UV light and photocatalyst target, creating an Advanced Oxidation Process containing several friendly oxidizers. Certified Space Technology continuously protects and purifies the air, and attacks contaminants on all surfaces.

Published scientific studies conducted on behalf of activTek by Dr. James Marsden at Kansas State University demonstrated that activTek's ActivePure Technology substantially reduces microbial populations on surfaces. The study's results are being provided solely for informational purposes. The study's results have not been reviewed by the FDA, EPA or any other governmental agency. Our products are not medical devices and are not intended to diagnose, treat, or cure any disease. We make no claims and no claims should be inferred as to the efficacy of our products to sanitize, disinfect or kill germs or other antimicrobials.

specifications

Air Scrubber by Aerus	9960051 • 9960052 (ozone free)*	
ozone production	0.00 ppm with ozone-free replaceable ActivePure® Cell	0.40 ppm maximum with ozone replaceable ActivePure Cell* (as measured at the device)
electrical	Input voltage: 24 Volts, 1A Current: 18 Watts	
mechanical	Distribution via air handler	safety switch installed
dimensions	8.5″H x 8.5″W x 11″D	21.59cm L x 21.59cm W x 27.94cm D
weight	3 lbs.	1.2 kilograms
operating temp	32 ^o F – 200 ^o F 93 ^o C	
coverage	Up to 2,000 sq. ft. Nominal; 3,000 sq. ft. Maximum	
warranty	Limited 5 year warranty	
*Orana free unit is CADB cartified and able to ship to California		

*Ozone free unit is CARB certified and able to ship to California



SINGLE ROOM AIR SYSTEM







2017 Space Technology Hall of Fame Inductee

description

- Compact, self contained, natural air treatment system
- Discreet internal mounting
- No cleaning required
- ActivePure® Technology
- Convenient power cord

applications

- Installs inside of the ductwork of "Stand-Alone" or typical "In-Wall" air handler units
- Hotel rooms
- Motel rooms
- Offices

the technology

The activTek INDUCT 500 utilizes tested ActivePure^{*} Technology to substantially reduce odors, visible smoke in the air, and treat contamination on surfaces. Designed to be installed inside the ductwork of an in-wall heating and air conditioning unit, INDUCT 500 is compact, self-contained, and requires no cleaning. Covers up to 500 square feet. Professional installation recommended. Our proprietary ActivePure® Technology uses light waves and a catalytic process to produce scrubber ions that remove dust particles from the air. Our Certified Space Technology continuously protects and purifies the air, and attacks contaminants on all surfaces.*

Published scientific studies conducted on behalf of activTek by Dr. James Marsden at Kansas State University demonstrated that activTek's ActivPure Technology substantially reduces microbial populations on surfaces. The study's results are being provided solely for informational purposes. The study's results have not been reviewed by the FDA, EPA or any other governmental agency. Our products are not medical devices and are not intended to diagnose, treat, or cure any disease. We make no claims and no claims should be inferred as to the efficacy of our products to sanitize, disinfect or kill germs or other antimicrobials.

INDUCT 500	9960043 • 9960042 (ozone free)	
electrical	Input Voltage: 15VDC, .1 Amps, 100 – 240 VAC, 50/60 HZ	Current: 5 Watts – Switching Power Supply
mechanical	retainer clip included	
dimensions	10.38″ L x 2.25″ W x 1.25″ H	28.37cm L x 5.72cm W x 3.175cm H
weight	2.9 lbs.	1.3 kilograms
hvac air blower	250 SCFM recommended air flow	
ozone production	0.40 ppm maximum with ozone replaceable UV bulb • 0	.00 ppm with ozone-free replaceable UV bulb
coverage	Up to 500 sq. ft.	
warranty	Limited 3 year warranty	



DUCT MOUNTED SYSTEM



description

- Duct or plenum installed natural air system
- Discreet or concealed installation
- 100/277 volt optional installation •
- UV bulb monitoring indicator included
- Low maintenance no cleaning required

applications

COMMERCIAL HVAC AIR PURIFICATION ENHANCEMENT SYSTEM

 $\langle \rangle$

- Installs into any HVAC system up to 3 tons or 1500 CFM . with accessible ducts
- **Residential homes**
- Apartments
- Small offices
- Elevators

the technology

The activTek INDUCT 750 substantially reduces odors, visible smoke in the air, and microbial populations on surfaces*, utilizing the patent pending ActivePure® Technology. ActivePure consists of a special UV light and photocatalyst target, creating an Advanced Oxidation Process containing several friendly oxidizers. Our proprietary

ActivePure® Technology uses light waves and a catalytic process to produce scrubber ions that remove dust particles from the air. Our Certified Space Technology continuously protects and purifies the air, and attacks contaminants on all surfaces.*

Published scientific studies conducted on behalf of activTek by Dr. James Marsden at Kansas State University demonstrated that activTek's ActivePure Technology substantially reduces microbial populations on surfaces. The study's results are being provided solely for informational purposes. The study's results have not been reviewed by the FDA, EPA or any other governmental agency. Our products are not medical devices and are not intended to diagnose, treat, or cure any disease. We make no claims and no claims should be inferred as to the efficacy of our products to sanitize, disinfect or kill germs or other antimicrobials.

INDUCT 750	US40659B • US40668B (ozone free)	
electrical	Inpute Voltage: 100/277 VAC, 50/60 HZ	Current: .17A 17 Watts
mechanical	UV bulb monitoring system install	safety interlock switch installed
dimensions	9.62" H x 9.62" W x 7.48" D	24cm L x 24cm W x 19cm D
weight	3 lbs.	1.2 kilograms
max temp	<200 ⁰ F	
coverage	Up to 750 sq. ft.	
warranty	Limited 3 year warranty	



DUCT MOUNTED SYSTEM



description

- Duct or plenum installed natural air system
- Discreet or concealed installation
- 100/277 volt optional installation •
- UV bulb monitoring indicator included
- Low maintenance no cleaning required

applications

HVAC ENVIRONMENTAL CONDITIONING SYSTEM

 $\langle \rangle$

- Installs into HVAC systems with accessible ducts
- **Residential homes**
- Apartments
- Small offices

the technology

The activTek INDUCT 2000 substantially reduces odors, visible smoke in the air, and microbial populations on surfaces*, utilizing the patent pending ActivePure technology. ActivePure consists of a special UV light and photocatalyst target, creating an Advanced Oxidation Process containing several friendly oxidizers.

Our proprietary ActivePure® Technology uses light waves and a catalytic process to produce scrubber ions that remove dust particles from the air. Our Certified Space Technology continuously protects and purifies the air, and attacks contaminants on all surfaces.*

Published scientific studies conducted on behalf of activTek by Dr. James Marsden at Kansas State University demonstrated that activTek's ActivePure Technology substantially reduces microbial populations on surfaces. The study's results are being provided solely for informational purposes. The study's results have not been reviewed by the FDA, EPA or any other governmental agency. Our products are not medical devices and are not intended to diagnose, treat, or cure any disease. We make no claims and no claims should be inferred as to the efficacy of our products to sanitize, disinfect or kill germs or other antimicrobials.

-		
INDUCT 2000	US40532 • US40663B (ozone free)	
electrical	Input Voltage: 100/277 VAC, 50/60 HZ	Current: .17A 19 Watts
mechanical	UV bulb monitoring system install	safety switch installed
dimensions	9.62″H x 9.62″W x 11.25″D	24.5cm L x 24.5cm W x 28.5cm D
weight	3 lbs	1.2 kilograms
max temp	200 ⁰ F	
coverage	Up to 2,000 sq. ft.	
warranty	Limited 3 year warranty	



description

- Duct or plenum installed natural air system
- Discreet or concealed installation
- 120/240 volt optional installation
- UV bulb monitoring indicator included
- Low maintenance no cleaning required

applications

- Installs into any building with challenging odor, visible smoke, or microbials on surfaces with existing ducts
- Restaurants
- Bars
- Businesses

the technology

The Induct 5000 substantially reduces odors, visible smoke from the air, and microbial populations on **surfaces**,* utilizing the patent pending ActivePure® Technology. ActivePure consists of a special UV light and photocatalyst target, creating an Advanced Oxidation Process containing several friendly oxidizers. Our proprietary ActivePure® Technology uses light waves and a catalytic process to produce scrubber ions that remove dust particles from the air. Our Certified Space Technology continuously protects and purifies the air, and attacks contaminants on all surfaces.*

Published scientific studies conducted on behalf of activTek by Dr. James Marsden at Kansas State University demonstrated that activTek's ActivePure technology substantially reduces microbial populations on surfaces. The study's results are being provided solely for informational purposes. The study's results have not been reviewed by the FDA, EPA or any other governmental agency. Our products are not medical devices and are not intended to diagnose, treat, or cure any disease. We make no claims and no claims should be inferred as to the efficacy of our products to sanitize, disinfect or kill germs or other antimicrobials.

INDUCT 5000	US40536 • US40664B (ozone free)	
electrical	Inpute Voltage: 120/240 VAC, 50/60 Hz	Current: 20 Watts
mechanical	UV bulb monitoring system installed	safety switch installed
dimensions	9″ W x 9″ H x 17″ L	23cm W x 23cm H x 43.2cm L
weight	4 lbs.	1.8 kilograms
max temp	< 200 °F	
coverage	Up to 5,000 sq. ft.	
warranty	Limited 3 year warranty	



DUCT MOUNTED SYSTEM





description

- Duct or plenum installed natural air system
- Discreet or concealed installation
- 120/240 volt optional installation
- UV bulb monitoring indicator included
- Low maintenance no cleaning required

applications

- Installs into any building with challenging odor, visible smoke, or microbials on surfaces with existing ducts
- Restaurants
- Bars
- Businesses

the technology

The Induct 10000 substantially reduces odors, visible smoke from the air, and microbial populations on **surfaces**,* utilizing the patent pending ActivePure® Technology. ActivePure consists of a special UV light and photocatalyst target, creating an Advanced Oxidation Process containing several friendly oxidizers. Our proprietary ActivePure® Technology uses light waves and a catalytic process to produce scrubber ions that remove dust particles from the air. Our Certified Space Technology continuously protects and purifies the air, and attacks contaminants on all surfaces.*

Published scientific studies conducted on behalf of activTek by Dr. James Marsden at Kansas State University demonstrated that activTek's ActivePure Technology substantially reduces microbial populations on surfaces. The study's results are being provided solely for informational purposes. The study's results have not been reviewed by the FDA, EPA or any other governmental agency. Our products are not medical devices and are not intended to diagnose, treat, or cure any disease. We make no claims and no claims should be inferred as to the efficacy of our products to sanitize, disinfect or kill germs or other antimicrobials.

INDUCT 10000	US40537 • US40662B (ozone free)	
electrical	Input Voltage: 120/240 VAC, 50/60 Hz	Current: 37 Watts
mechanical	UV bulb monitoring system installed	safety switch installed
dimensions	11″ W x 11″ H x 17″ L	28cm W x 28cm H x 43.2cm L
weight	8 lbs	3.6 kilograms
max temp	200 °F	
coverage	Up to 10,000 sq. ft.	
warranty	Limited 3 year warranty	





PORTABLE WHOLE HOME/OFFICE SYSTEM



description

- Self contained, portable, multiple technologies, whole home/ office air system
- Plugs into standard 120VAC outlet
- Adjustable purifier control and fan speed
- LCD status display of machine
- All settings are remote control adjusted only
- · Away mode features with adjustable digital timer
- 5 speed fan control; 12 step purifier control

applications

 For reduction or removal of typical indoor air pollutants such as: visible smoke, odors, and microbials on surfaces*

AP3000

SPACE

- Removes dirt and dust from the air
- Freshens air and removes odors
- School classrooms
- Nursing homes
- Public lobbies and waiting rooms

the technology

The AP3000 substantially reduces odors, visible smoke from the air, and microbial populations on **surfaces**,* commonly found in the average home or office environment. AP3000 also utilizes needlepoint ionization, pulsating negative/positive ion field generator,

corona discharge air freshener, and the patent pending ActivePure® Technology – consisting of a special UV light and photocatalyst target – thereby creating an Advanced Oxidation Plasma containing several friendly oxidizers.

*Published scientific studies conducted on behalf of activTek by Dr. James Marsden at Kansas State University demonstrated that activTek's ActivePure" Technology substantially reduces microbial populations on surfaces. The study's results are being provided solely for informational purposes. The study's results have not been reviewed by the FDA, EPA or any other governmental agency. Our products are not medical devices and are not intended to diagnose, treat, or cure any disease. We make no claims and no claims should be inferred as to the efficacy of our products to sanitize, disinfect or kill germs or other antimicrobials.

specifications

AP3000 • AP3000 II	9940040 • 9940039 (ozone free)*	
electrical	Input Voltage: 100 \sim 240 VAC 50/60 Hz External Power Supply \mid 48 watts	Current: 50 Watts Max
mechanical	40-60 CFM Fan, Washable electrostatic lint screen	computer style cord
dimensions	12" H x 9" W x 12" D	30.5cm H x 23cm W x 30.5cm D
weight	10.2 lbs.	4.62 kilograms
coverage	250 sq. ft. to 3,000 sq. ft.	
warranty	Limited 3 year warranty	

*Ozone free unit is CARB certified and able to ship to California



description

- · Compact, natural air treatment system not a filter
- Plugs into existing 120 volt outlet
- No wiring required
- No cleaning required
- Standard 120 VAC outlet on side of unit
- Removable, washable lint screen

applications

- Ideal for small or isolated indoor pollution and odorcausing areas
- Waiting rooms or small lobbies
- Hotel rooms
- Nursing home rooms
- Public restrooms

the technology

Powerful and inconspicuous, the AP500 system is designed to target smaller rooms with the benefits ActivePure®. The AP500 works as a stand-alone unit or as companion to the AP3000 or Air Scrubber by Aerus units for more complete treatment. AP500 utilizes ActivePure® Technology to effectively treat interior air and exposed surfaces. Our proprietary ActivePure® Technology uses light waves and a catalytic process to produce scrubber ions that remove dust particles from the air. Our Certified Space Technology continuously protects and purifies the air, and attacks contaminants on all surfaces.*

Published scientific studies conducted by Dr. James Marsden at Kansas State University demonstrated that ActivePure Technology substantially reduces microbial populations on surfaces. The study's results are being provided solely for informational purposes. The study's results have not been reviewed by the FDA, EPA, or any other governmental agency. Our products are not medical devices and are not intended to diagnose, treat, or cure any disease. We make no claims and no claims should be inferred as to the efficacy of our products to sanitize, disinfect, or kill germs or other antimicrobials.

specifications

AP500	00693	
electrical	Input Voltage: 120V~, 60 Hz, .18 amp	Current: 13 Watts
mechanical	One control switch	on/off
dimensions	6″W x 12″H x 4″D	15.24cm W x 30cm H x 10cm D
weight	2.9 lbs.	1.3 kilograms
coverage	Up to 500 sq. ft.	
warranty	Limited 3 year warranty	

Our products are not medical devices and are not intended to diagnose, treat, or cure any disease. We make no claims and no claims should be inferred as to the efficacy of our products to sanitize, disinfect or kill germs or other antimicrobials.





INNOVATIVE AIR TREATMENT SYSTEM

ActivePure



Hall of Fame Inductee



Made in t

description

- Natural air system assembled onto the mini-split/HVAC system
- Discreet or concealed installation
- Low maintenance no cleaning required
- Requires only 20 watts of electricity
- Made in the U.S.A.

applications

Air Scrubber

Mounts externally onto existing mini-split/HVAC system

- Residential homes
- Apartments
- Small offices
- Efficiency apartments
- Nursing homes
- Protects mini-split heating and cooling systems from dust buildup

the technology

The Air Scrubber Mini EM by Aerus is an innovative, ozone-free, air treatment system that easily mounts externally onto existing Mini Split HVAC systems. When the Air Scrubber Mini EM by Aerus is properly installed and activated, advanced oxidizers are released into the air that immediately begin reducing airborne pollutants. Our proprietary ActivePure® Technology uses light waves and a catalytic process to produce scrubber ions that remove dust particles from the air. Our Certified Space Technology continuously protects and purifies the air, and attacks contaminants on all surfaces.*

Published scientific studies conducted on behalf of activTek by Dr. James Marsden at Kansas State University demonstrated that activTek's ActivePure Technology substantially reduces microbial populations on surfaces. The study's results are being provided solely for informational purposes. The study's results have not been reviewed by the FDA, EPA or any other governmental agency. Our products are not medical devices and are not intended to diagnose, treat, or cure any disease. We make no claims and no claims should be inferred as to the efficacy of our products to sanitize, disinfect or kill germs or other antimicrobials.

-		
Air Scrubber Mini EM by Aerus	9960022	
electrical input	Input Voltage: 230 VAC	Current: 0.2A @ 120 VAC Power Factor: 0.99 Power: 20 Watts max
mechanical	Distribution via air handler	
operating temperature	23F-131°F (-5° C to 55° C)	
dimensions	29.75" L x 2.63" W x 1.25" H	75.57 cm L x 6.67 cm W x 3.18 cm H
coverage	Up to 500 sq. ft.	
warranty	Limited 2 year warranty	

PURECLOUD

INNOVATIVE AIR TREATMENT SYSTEM

ActivePure E C H NOLDORY Adde in the USA Adde in the USA Ball of Fame Inductes

description

- 2 x 2 foot drop-in ceiling unit
- Natural air purifier with ActivePure® Technology
- Installed by a professional electrician
- Cleans up to 2,000 square feet of air per hour
- Low maintenance
- Discreet installation

applications

- Designed to be mounted into a ceiling
- · Educational and childcare facilities
- · Residential and assisted living environments
- Business offices and professional buildings
- Public lobbies and waiting rooms

the technology

PureCloud substantially reduces odors, visible smoke from the air, and microbial populations on **surfaces**,* commonly found in the air of a variety of indoor living and working environments. PureCloud utilizes ActivePure* Technology – consisting of a special UV light and photocatalyst target – thereby creating an Advanced Oxidation Plasma containing several friendly oxidizers. Our Certified Space Technology continuously protects and purifies the air, and attacks contaminants on all surfaces.*

Published scientific studies conducted by Dr. James Marsden at Kansas State University demonstrated that ActivePure Technology substantially reduces microbial populations on surfaces. The study's results are being provided solely for informational purposes. The study's results have not been reviewed by the FDA, EPA, or any other governmental agency. Our products are not medical devices and are not intended to diagnose, treat, or cure any disease. We make no claims and no claims should be inferred as to the efficacy of our products to sanitize, disinfect, or kill germs or other antimicrobials.

PureCloud	9960023 (120V) • 9960026 (230V)
electrical	110-120V 60Hz .75A (90W) 220V - 240V 50Hz 0.3A
mechanical	100CFM (Fan) 2.83 m ³ /min, impedance-protected motor, UV-C bulb, 26 watts, safety power switch
coverage	Up to 2,000 sq. ft. per hour
dimensions	24" H x 24" W x 5" D, (60.96cm H x 60.96cm W x 12.7cm D)
weight	12 lbs., (5.44 kilograms)
coverage	Up to 2,000 sq. ft.
warranty	Limited 3 year warranty



G4 WHOLE HOME FILTRATION

WHOLE HOME FILTRATION SYSTEM



description

- Whole home purification system
- 2 stage filtration cleans up to 3,000 sq. ft.
- Powerful brushless motor for quiet operation and long life
- Cleans the air 24 hours a day, even when your HVAC system is not on
- Activated carbon filter absorbs odors
- Low maintenance
- · Pre-filter needs to be replaced every 12 months
- HEPA filter needs to be replaced every 2 years

the technology

Ensure air quality with the G4 Whole Home Filtration System. Installed directly to the HVAC system ductwork to clean the air as it passes through the system, the G4 is a True HEPA filtration system, removing 99.97% of harmful particles as small as 0.3 micron, and powerfully

protecting the air in any environment 24/7. The G4 is the perfect solution for homeowners and businesses that want to eliminate harmful air particles.

specifications

G4 Whole Home Filtration System F193A	00646
air flow	300 cfm
weight	44 lbs
input voltage	120 VAC 60 Hz
current (without Air Scrubber by Aerus attached)	0.9 Amps • 108 Watts
current (with Air Scrubber by Aerus attached)	1.0 Amps • 127 Watts
operating temp. range - return air (°F)	30 to 95
system HEPA filter efficiency	99.97% @ 0.3 micron particles
air intake collar	8" round
air outflow collar	6" round
dimensions	20.75" W x 19.75" H x 20.00" D $$ (52.71 cm W x 50.17 cm H x 50.8 cm D $$
coverage	Up to 3,000 sq. ft.
warrany	Limited 5 year warranty



applications

- Installs into HVAC systems with accessible ducts as its own self-contained unit
- Residential homes
- Apartments
- Offices

LAUNDRY PRO 2.0

A BEYOND BY AERUS TECHNOLOGY

THE SMART SOLUTION FOR DOING LAUNDRY

2017 Space Technology Hall of Fame Inductee Made in the USA

description

ActivePure

- No Need For Detergent*
- Makes Clothes Softer
- Clean Without Bleach
- No Worries and No Maintenance
- Better For Sensitive Skin
- Monitors operation with blue LED indicator
- Made in USA

the technology

Laundry Pro 2.0 incorporates the power of our revolutionary, exclusive ActivePure® Technology with the cleaning action of water with hydrogen and oxygen-based oxidizers to lift dirt and grime away from the fibers of fabric and prevent the growth of odor-causing bacteria. Laundry Pro 2.0 is an amazingly effective cold water laundry system for residential use. Laundry Pro 2.0 ensures that you aren't absorbing anything from the fabrics you touch, which helps you to avoid the allergic reactions that can be caused by detergents. Based on processes used for over a decade in hospitals, hotels, and laundromats, Laundry Pro 2.0 infuses cold water hydrogen and oxygen-based oxidizers bubble and lift dirt and grime from cloth fibers, leaving clothes brighter and cleaner.

*NOTE: Laundry Pro 2.0 reduces or eliminates the need for laundry detergent. While many users find that Laundry Pro 2.0 alone effectively cleans their laundry, you may find it necessary to pre-treat or use a reduced amount of detergent to remove certain stains. If you find that detergent is necessary, we recommend using 1/8th the amount you previously used before your Laundry Pro 2.0 purchase.

specifications

Laundry Pro 2.0	00695
power consumption	0.4W AC (standby mode); 1.3W AC (operating)
power adapter input	AC in: 100-240V ~50/60 Hz 0.45A
power adapter output	DC out: 12V 2.5A
water pressure	Min. 20 psi to 60 psi Max. 1.37 ~ 4.13 bar
water temperature	use cold water only (do not use hot water)
operating environment	50°F to 100°F (10°C - 37.8°C)
operating humidity	40% to 85%
dimensions	17.3″W x 5.19″H x 3.69″D
weight	4.31 lbs
warranty	Limited 3 year warranty



applications

- Cold Water Laundry System
- Ease of Use
- Easy to Install
- Earth-Friendly
- Whiter Whites, Brighter Colors
- Certified Space Technology

\$149.00

Air Scrubber MOBILE BY AERUS

WITH CERTIFIED SPACE TECHNOLOGY[™]

PORTABLE ELECTRONIC PURIFIER



description

- ActivePure Technology[®] destroys up to 99% of surface and airborne contaminants
- Reduces airborne contaminants and allergens reducing asthma and allergy symptoms for a healthier body
- Freshens air and removes odors in otherwise stale-prone
 environments
- Reduces dirt and dust from the air to make cleaning easier
- Touch sensitive settings for ease of operation and function
- Multiple settings to customize and optimize for use in multiple
 environments

the technology

The Air Scrubber Mobile by Aerus is a pocket-sized unit that significantly reduces unpleasant odors, contaminants and allergens by utilizing ActivePure[®] Technology, which features a high intensity applications

- Small and large automobiles
- R.V.'s
- Campers
- Hotels and motels

UVC lighting. The Air Scrubber Mobile by Aerus is ideal for providing the cleanest, healthiest air for your car, truck, R.V. or camper.

Air Scrubber Mobile by Aerus	US40672B
electrical	12VDC or 110 - 240 VAC 50/60Hz with adapter
operation temperature	45°F - 100°F (7°C - 38°C)
power usage	Maximum 10.7 watts
fuse	2 amp Buss type (12VDC adapter only)
dimensions	3.625" x 6" x 1.0" (9.21cm x 15.25cm x 2.54cm) w/o base
weight	8 ounces (.23kg)
coverage	Up to 500 sq. Ft.
warranty	Limited 1-year warranty



AERUS CORPORATE HEADQUARTERS | DALLAS, TX





AERUS MANUFACTURING PLANT | BRISTOL, VA